

INDUSTRIAL COMPONENT DATA

THERMOMARK CARD 2.0 1085267 PHOENIX CONTACT The THERMOMARK CARD 2.0 thermal transfer printer quickly prints ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: THERMOMARK CARD 2.0



Manufacturer	PHOENIX CONTACT
MPN / Reference	THERMOMARK CARD 2.0
Catalog number	1085267
Category	Printer/scanner/copier
Minimum order	1 Pcs
Document ID	EO-ADB68BBDDDE
Generated	2026-08-06

Product Overview

The THERMOMARK CARD 2.0 thermal transfer printer quickly prints high-quality marking materials in card and mat format. Create high-quality markers for terminal, conductor, cable, equipment, and facility marking applications.

Thermal transfer printer for card-on-card materials, including Europe/US power cable and USB cable. Printed user manual in German and English. Charger for UCT-TM boards... and charger for US cards... For each packaging unit UCT-TM 6, US-EMLP (85.6x54), ink roll = 50 m

Thermal transfer printer for card materials, including Euro/US power cable and USB cable. Support CD includes user manuals in several languages, links to firmware, drivers, and planning and marking software. User manual printed in German and English. Magazine for UCT-TM... sheets and magazines for US-... cards. One Pcs./Pkt. each UCT-TM 6, US-EMLP (85,6x54), ink ribbon = 50 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS devices / software
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1085267

Packing unit 1 pc

Catalog page Page 35 (C-3-2019)

GTIN 4055626834931

Weight per Piece (excluding packing) 9,980.000 g

Custom tariff number 84433210

Country of origin DE (Germany)

General

Connection data

Classifications

Dimensions

Environmental Product Compliance

General

Interface 10/100 Mbps Ethernet

USB 2.0

Weight 6 kg

[Back to top](#)Dimensions

Length 325 mm

Height 194 mm

Width 254 mm

[Back to top](#)Connection data

Minimum voltage 100 V AC

Max. voltage 240 V AC

Additional text 50 Hz ... 60 Hz

[Back to top](#)Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 10;

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

[Back to top](#)Classifications

ECLASS

ECLASS 10.0.1 19140104

ECLASS 11.0 19140104

ECLASS 4.0 24010402

ECLASS 4.1 24010402

ECLASS 5.0 19020207

ECLASS 5.1 19020200

ECLASS 6.0 19140100

ECLASS 7.0 19140104

ECLASS 9.0 19140104

[Back to top](#)ETIM

ETIM 2.0 EC000761

ETIM 3.0 EC000761

ETIM 4.0 EC001672

ETIM 6.0 EC001672

ETIM 7.0 EC001672

[Back to top](#)UNSPSC

UNSPSC 6.01 43172501

UNSPSC 7.0901 43212107

UNSPSC 11 43172501

UNSPSC 12.01 43212107

UNSPSC 13.2 43212108

UNSPSC 18.0 43212108

UNSPSC 19.0 43212108

UNSPSC 20.0 43212108

UNSPSC 21.0 43212108

Back to top

ETIM for 1085267 Telecoms and office equipment (EC001684)

Feature Name

Feature Value

Printer (EF002805)

Yes

Scanner (EF005223)

No

Fax (EF004680)

No

Photocopier (EF004853)

No

Print process (EF000727)

Therm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / THERMOMARK CARD 2.0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.