

**INDUSTRIAL COMPONENT DATA**

# TML (EX4,2)R P10 TR CUS 0852162 PHOENIX CONTACT

## Marking foil for zack marker strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: TML (EX4,2)R P10 TR CUS



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | PHOENIX CONTACT              |
| MPN / Reference | TML (EX4,2)R P10 TR CUS      |
| Catalog number  | 0852162                      |
| Category        | Labelling for terminal block |
| Minimum order   | 1 Pcs                        |
| Document ID     | EO-322F9EC160                |
| Generated       | 2026-08-05                   |

### Product Overview

Marking foil for zack marker strip

Marking film for Zack strip, Roll, available: by lines, transparent, labeled according to customer indications, labelable with: THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting class: glued, for terminal width: 10 mm, useful surface: 40000 x 4.2mm

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                  |
|--------------|----------------------------------|
| Catalog path | PHOENIX CONTACT > CABINET add-on |
|--------------|----------------------------------|

### Additional Product Information

Key Commercial Data

Orderkey 0852162

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356355384

Weight per Piece (excluding packing) 1.990 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 40 m

Width (a) 4.2 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

General

Color transparent

Type adhesive

Components Silicone-free

Material Polyester

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Marking mounting type adhesive

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Classifications

eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027141137eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss  
7.027141137eCl@ss 8.027141137eCl@ss 9.027141137

ETIM 3.0EC000761ETIM 4.0EC000761ETIM 5.0EC000761ETIM 6.0EC000761

UNSPSC 6.0130211811UNSPSC 7.090139121410UNSPSC 1139121410UNSPSC 12.0139121410UNSPSC  
13.239131505

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TML (EX4,2)R P10 TR CUS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.