

INDUSTRIAL COMPONENT DATA

TML (EX4,2)R P5 TR CUS 0852165 PHOENIX CONTACT Film lettering to strip Zack, available: by line, transparent..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TML (EX4,2)R P5 TR CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	TML (EX4,2)R P5 TR CUS
Catalog number	0852165
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-432F5C34A3
Generated	2026-08-06

Product Overview

Film lettering to strip Zack, available: by line, transparent, labeled according to customer requirements, mounting Type: Glued, usable Area: 40000 x 4.2 mm

Marking film for Zack strip, Roll, available: by lines, transparent, labeled according to customer indications, labelable with: THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting class: glued, for terminal width: 5 mm, useful surface: 40000 x 4.2mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Data commercial

Key order 0852165

Packing unit 1 pcs

Key selling BG8111 -

Note Manufacturing under the order. (No refund)

EAN Four trillion forty six billion three hundred fifty six million three hundred fifty five thousand four hundred fourteen

Unit weight (excluding packaging) 1,990 g

Tariff number tariff Forty nine million one hundred nineteen thousand nine hundred

Country of origin (Germany)

Measures

Length (b) 40 m

Width (a) 4.2 mm

Environmental conditions

Room temperature (service) -40 °C ... 150 °C

Overview

Color transparent

Execution stuck

Substances contained Without silicone

Material Polyester

Resistance to the cleaned DIN EN 61010-1 (VDE 0411-1)

Mounting type, marking stuck

Standards and specifications

Resistance to the cleaned DIN EN 61010-1 (VDE 0411-1)

Ratings

eCl@ss 4.0Twenty four million one hundred ninety thousand two hundred nineteeneCl@ss 4.1Twenty four million one hundred ninety thousand two hundred nineteeneCl@ss 5.0Twenty seven million one hundred forty one thousand one hundred thirty seveneCl@ss 5.1Twenty seven million one hundred forty one thousand one hundredeCl@ss 6.0Twenty seven million one hundred forty one thousand one hundredeCl@ss 7.0Twenty seven million one hundred forty one thousand one hundred thirty seveneCl@ss 8.0Twenty seven million one hundred forty one thousand one hundred thirty seveneCl@ss 9.0Twenty seven million one hundred forty one thousand one hundred thirty seven

ETIM 3.0EC000761ETIM 4.0EC000761ETIM 5.0EC000761ETIM 6.0EC000761

UN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TML (EX4,2)R P5 TR CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.