

INDUSTRIAL COMPONENT DATA

TML (EX7)R SR CUS 0830851 PHOENIX CONTACT Marking foil for zack marker strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: TML (EX7)R SR CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	TML (EX7)R SR CUS
Catalog number	0830851
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-99F75A742B
Generated	2026-08-04

Product Overview

Marking foil for zack marker strip

Zack strip wrapping film, Roll, available: by lines, silver, labeled according to customer's instructions, labelable with: THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting class: glued, for terminal width: 30000 mm, usable area: 30000 x 7 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0830851

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356897341

Weight per Piece (excluding packing) 1.990 g

Custom tariff number 39199080

Country of origin DE (Germany)

Dimensions

Length (b) 30 m

Width (a) 7 mm

Ambient conditions

Recommended storage conditions 23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing.

General

Color silver

Type adhesive

RoHS compliant Yes

Adhesive Acrylic

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146231 THERMOMARK X1.2

Ink ribbon 5145384 THERMOMARK-RIBBON 110

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Foil strength 53 µm

Adhesive strength 20 µm

Marking mounting type adhesive

Classifications

eCl@ss 4.124190208eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss 7.027141137eCl@ss 8.027141137eCl@ss 9.027141137

ETIM 4.0EC000761ETIM 5.0EC000761ETIM 6.0EC000761

UNSPSC 13.239131505

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TML (EX7)R SR CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.