

INDUSTRIAL COMPONENT DATA

TP090SKW/200114031 S00122 1082740 PHOENIX CONTACT

Touch panel with 22.9 cm/9" TFT-display (Projective-capaci..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TP090SKW/200114031 S00122



Manufacturer	PHOENIX CONTACT
MPN / Reference	TP090SKW/200114031 S00122
Catalog number	1082740
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-99AB16B738
Generated	2026-08-04

Product Overview

Touch panel with 22.9 cm/9" TFT-display (Projective-capacitive, four-touch control), 800 x 480 pixel(s) (WVGA), 16.7 million colors, Arm

Touch panel with 22.9 cm / 9"-TFT-display (projective-capacitive, four-point use), 800 x 480 pixel(s) (WVGA), 16.7 million colors, Arm®Cortex®-A8, 1000 MHz, 2x USB Host 2.0, 1x Ethernet (10/100 MBits/s), RJ45, Windows®Embedded Compact 7 and user software: Visu+. (Bus system: SIN)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Control Systems (CST)**

Additional Product Information

Key Commercial Data

Orderkey 1082740

Packing unit 1

GTIN 4055626817019

Custom tariff number 84714100

Note

Display

General

Device supply

Classifications

Dimensions

[Computer data](#)

[Ambient conditions](#)

[Standards and Regulations](#)

[Note](#)

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

[Back to top](#)[Dimensions](#)

Outer dimensions: width, height, depth 304 mm x 194 mm x 5 mm (Dimensions of the front plate)

Installation dimensions: width, height, depth 268 mm x 158 mm x 57 mm (Mounting cutout, depth with bus if bus system present in the device)

[Back to top](#)[Display](#)

Display 22.9 cm/9" TFT

Screen resolution 800 x 480 Pixel(s) (WVGA)

Touch technology Projective-capacitive, four-touch control

Brightness 800 cd/m², typical (adjustable)

Backlighting LED

Display backlight MTBF 70000 h

Colors 16.7 million colors

Reading angle left 85 °

Reading angle right 85 °

Reading angle top 85 °

Reading angle bottom 85 °

[Back to top](#)[Computer data](#)

Processor Arm®Cortex®-A8, 1000 MHz

Operating system Windows®Embedded Compact 7

User software Visu+

RAM 1 MB SRAM

512 MB LPDDR RAM

Mass storage NAND-Flash, 1 GB

Network 1 x Ethernet (10/100 Mbps), RJ45

Interfaces 2x USB Host 2.0

Bus system without

Slots 1x SD

Realtime clock Yes

Service life of battery 5 years (typical)

[Back to top](#)[General](#)

Housing material Steel sheet, zinc-plated

Mounting type Front installation (open frame, optimized for 2 mm sheet thickness)

Weight 2120 g

[Back to top](#)[Ambient conditions](#)

Degree of protection IP65...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TP090SKW/200114031 S00122 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.