

INDUSTRIAL COMPONENT DATA

MCR-SL-S-400-I-LP 2813509 PHOENIX CONTACT Current transducers

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCR-SL-S-400-I-LP



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCR-SL-S-400-I-LP
Catalog number	2813509
Category	Current value transformer
Minimum order	1 Pcs
Document ID	EO-A3FE3993FD
Generated	2026-08-04

Product Overview

Current transducers

MCR current converter, for measuring sinusoidal and non-sinusoidal alternating currents, input current 0...400 A, Loop-powered output with 4...20 mA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2813509

Packing unit 1 pc

Catalog page Page 395 (IF-2009)

GTIN 4046356043687

Weight per Piece (excluding packing) 143.000 g

Custom tariff number 85437090

Country of origin JP (Japan)

Dimensions

Primary round conductor (diameter) 18.5 mm

Width 55 mm

Height 85 mm

Depth 70.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C

Input data

Input Current measuring input

Input current range 0 A ... 400 A (0 ... 200/300/400 A)

Operate threshold 1 % (of final value)

Setting range for min. input current 0 A ... 200 A

Setting range for max. input current 0 A ... 400 A

Overload capacity Depending on laid conductor

Surge strength Depending on through connected conductor

Frequency measuring range 30 Hz ... 6000 Hz

Output data

Output name Current output

Current output signal 4 mA ... 20 mA

Max. output current < 25 mA

Load/output load current output (UB- 12 V) x 350 / 12 A

Switching output

Output name No switching output

Power supply

Supply voltage range 20 V DC ... 30 V DC

Connection data

Connection method Pluggable screw connection

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 14

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Stripping length 8 mm

Screw thread M3

General

Maximum transmission error < 1 % (of final value)

Maximum temperature coefficient < 0.025 %/K

Step response (10-90%) < 340...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCR-SL-S-400-I-LP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.