

INDUSTRIAL COMPONENT DATA

TRIO-PS-2G/3AC/24DC/40 2903156 PHOENIX CONTACT Power supply unit

Brand: PHOENIX CONTACT | Manufacturer Part Number: TRIO-PS-2G/3AC/24DC/40



Manufacturer	PHOENIX CONTACT
MPN / Reference	TRIO-PS-2G/3AC/24DC/40
Catalog number	2903156
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-98412AF656
Generated	2026-08-04

Product Overview

Power supply unit

Primary-switched TRIO power supply for rail mounting, input: three-phase, output: 24 V DC/40 A, dynamic boost, tool-free quick connect technology for rigid and flexible cables with ferrule

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Power Supplies (PS)

Additional Product Information

Key Commercial Data

Orderkey 2903156

Packing unit 1 pc

Catalog page Page 223 (C-4-2017)

GTIN 4046356960977

Weight per Piece (excluding packing) 2,850.000 g

Custom tariff number 85044030

Country of origin CN (China)

Dimensions

Width 110 mm

Height 130 mm

Depth 160 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -25 °C ... 70 °C (> 60 °C Derating: 2.5 %/K)

Ambient temperature (start-up type tested) -40 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) ≤ 95 % (at 25 °C, non-condensing)

Climatic class 3K3 (in acc. with EN 60721)

Degree of pollution 2

Installation height ≤ 4000 m (> 2000 m, Derating: 10 %/1000 m)

Input data

Nominal input voltage range 3x 400 V AC ... 500 V AC

Input voltage range 3x 400 V AC ... 500 V AC -20 % ... +15 %

AC frequency range 50 Hz ... 60 Hz

Discharge current to PE < 3.5 mA

Current consumption 3x 1.9 A (400 V AC)

3x 1.7 A (500 V AC)

Nominal power consumption 1335.1 VA

Inrush surge current ≤ (typical)

Mains buffering typ. 10 ms (400 V AC)

typ. 20 ms (500 V AC)

Input fuse 6.3 A (internal (device protection))

Choice of suitable circuit breakers 10 A ... 16 A (Characteristics B, C, D, K)

Power factor (cos phi) 0.77

Type of protection Transient surge protection

Protective circuit/component Varistor

Output data

Nominal output voltage 24 V DC ±1 %

Setting range of the output voltage (USet) 24 V DC ... 28 V DC (> 24 V DC, constant capacity restricted)

Nominal output curren...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TRIO-PS-2G/3AC/24DC/40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.