

INDUSTRIAL COMPONENT DATA

TRIO-PS-IP67/3AC/24DC/20 1039829 PHOENIX CONTACT

TRIO POWER primary-switched power supply in IP67 die-cast h..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TRIO-PS-IP67/3AC/24DC/20



Manufacturer	PHOENIX CONTACT
MPN / Reference	TRIO-PS-IP67/3AC/24DC/20
Catalog number	1039829
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-8C7913E015
Generated	2026-08-06

Product Overview

TRIO POWER primary-switched power supply in IP67 die-cast housing, input: 3-phase, output: 24 V DC / 20 A
TRIO POWER primary switching power supply in IP67 die-cast housing, input: three-phase, output: 24 V DC/20 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Power Supplies (PS)
--------------	---------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1039829

Packing unit 1

Catalog page Page 265 (C-4-2019)

GTIN 4055626595795

Custom tariff number 85044030

Drawings

Ambient conditions

Output data

Connection data, input

Connection data for signaling

EMC data

Classifications

Dimensions

Input data

General

Connection data, output

Standards

Environmental Product Compliance

Drawings

Block diagram

Back to topDimensions

Width 151 mm

Height 304 mm

Depth 120 mm

Back to topAmbient conditions

Degree of protection IP67

Ambient temperature (operation) -25 °C ... 85 °C (Derating > 60 °C (3 AC): 2,5 %/K / > 50 °C (2 AC): 2,5 %/K)

Ambient temperature (start-up type tested) -40 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) ≤ 95 % (at 25 °C, non-condensing)

Climatic class 3K3 (in acc. with EN 60721)

Degree of pollution 4

Installation height ≤ 4000 m (> 2000 m, Derating: 10 %/1000 m)

Back to topInput data

Nominal input voltage range 3x 400 V AC ... 500 V AC

2x 400 V AC ... 500 V AC

Input voltage range 3x 400 V AC ... 500 V AC -20 % ... +15 %

2x 400 V AC ... 500 V AC -10 % ... +15 %

AC frequency range 50 Hz ... 60 Hz

Discharge current to PE < 3.5 mA

Current consumption 3x 1.2 A (400 V AC)

3x 1 A (500 V AC)

2x 2.3 A (400 V AC)

2x 1.9 A (500 V AC)

Nominal power consumption 39 W

Inrush current typ. 22 A (at 25 °C)

Mains buffering time typ. 10 ms (400 V AC)

typ. 20 ms (500 V AC)

Input fuse 3.15 A (internal (device protection), slow-blow)

Recommended breaker for...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TRIO-PS-IP67/3AC/24DC/20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.