

INDUSTRIAL COMPONENT DATA

TRIO2-DIODE/12-24DC/2X10/1X20 2907380 PHOENIX CONTACT Diode

Brand: PHOENIX CONTACT | Manufacturer Part Number: TRIO2-DIODE/12-24DC/2X10/1X20



Manufacturer	PHOENIX CONTACT
MPN / Reference	TRIO2-DIODE/12-24DC/2X10/1X20
Catalog number	2907380
Category	Surge protection module
Minimum order	1 Pcs
Document ID	EO-4241249691
Generated	2026-08-05

Product Overview

Diode

Redundancy module, 12 V - 24 V DC, 2x 10 A, 1x 20 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Power Supplies (PS)**

Additional Product Information

Technical dataInput dataDC operation

Nominal input voltage range 12 V DC ... 24 V DC

Input voltage range 10 V DC ... 30 V DC

Voltage type of supply voltage DC

Reverse polarity protection < yes60 V

Nominal input current (IN) 2x 10 A (-25 °C ... 60 °C)

1x 20 A (-25 °C ... 60 °C)

Maximum current I_{max} 2x 15 A (-25 °C ... 40 °C)

1x 30 A (-25 °C ... 40 °C)

Nominal input current (IN) 2x 10 A (-25 °C ... 60 °C)

1x 20 A (-25 °C ... 60 °C)

Transient surge protection Varistor

Voltage drop, input/output 0.5 V

Output dataEfficiency > 97 %

Nominal output voltage U_{In} - 0,5 V
Nominal output current (IN) 20 A
10 A
Derating 60 °C ... 70 °C (2.5 %/K)
Power loss nominal load max. 5 W (I_{OUT} = 10 A)
Connection in series no
Derating 60 °C ... 70 °C (2.5 %/K)
Connection dataInput
Connection method Push-in connection
Conductor cross section, rigid min. 0.2 mm²
Conductor cross section, rigid max. 4 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG min. 16
Conductor cross section AWG max. 12
Stripping length 10 mm
Output
Connection method Screw connection
Conductor cross section, rigid min. 0.2 mm²
Conductor cross section, rigid max. 10 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 6 mm²
Conductor cross section AWG min. 12
Conductor cross section AWG max. 8
Stripping length 15 mm
Screw thread M3
Tightening torque, min 0.5 Nm
Tightening torque max 0.6 Nm
Electrical propertiesInsulation volt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TRIO2-DIODE/12-24DC/2X10/1X20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.