

INDUSTRIAL COMPONENT DATA

TTC-6-FC-UT 1054762 PHOENIX CONTACT Fuse carrier for surge protective devices of the TERMITRAB complete prod..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TTC-6-FC-UT



Manufacturer	PHOENIX CONTACT
MPN / Reference	TTC-6-FC-UT
Catalog number	1054762
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-A6FEC09F0F
Generated	2026-08-06

Product Overview

Fuse carrier for surge protective devices of the TERMITRAB complete product range with screw connection technology. Multi-level connection on TTC-6 housings possible. For conventional 5x20 mm miniature fuses.

Fuse holders for surge protection devices from the TERMITRAB product line complete with screw connection technology. Possibility of connecting several floors to TTC-6 boxes. For fuses for weak currents 5x20 mm commonly used.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1054762

Packing unit 1 pc

Catalog page Page 127 (C-4-2019)

GTIN 4055626690896

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85363010

Country of origin DE (Germany)

Drawings

Ambient conditions

Protective circuit

Standards and Regulations

Dimensions

General

Connection data

Classifications

Drawings

Dimensional drawing

[Back to top](#)Dimensions

Height 24 mm

Width 6.2 mm +0.1 mm

Depth 47 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Altitude ≤ 4000 m (amsl (above mean sea level))

Degree of protection IP20

[Back to top](#)General

Housing material PBT

Flammability rating according to UL 94 V-0

Color traffic grey A RAL 7042

Mounting type Snapping and screwing components onto TERMITRAB complete

[Back to top](#)Protective circuit

Operating voltage range 60 V DC

Rated current 6.3 A

[Back to top](#)Connection data

Connection method Screw connection

Screw thread M3

Tightening torque 0.5 Nm

Stripping length 8 mm

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section AWG 24 ... 12

[Back to top](#)Standards and Regulations

Standards/specifications EN 60947-7-3 2009

[Back to top](#)Classifications

eCl@ss

eCl@ss 8.0 27130890

eCl@ss 9.0 27130890

[Back to top](#)ETIM

ETIM 5.0 EC002497

ETIM 6.0 EC002497

ETIM 7.0 EC002497

[Back to top](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TTC-6-FC-UT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.