

INDUSTRIAL COMPONENT DATA

TTC-6P-3-5DC-PT-I 1061385 PHOENIX CONTACT Surge protection, consisting of protective plug and base element, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TTC-6P-3-5DC-PT-I



Manufacturer	PHOENIX CONTACT
MPN / Reference	TTC-6P-3-5DC-PT-I
Catalog number	1061385
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-7A2DF6AA01
Generated	2026-08-06

Product Overview

Surge protection, consisting of protective plug and base element, with integrated status indicator for a 3-wire floating signal circuit with high nominal current.

Surge protection consisting of plug-in protection and base element with integrated status indication for a floating 3-wire signal circuit with high rated current.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data

Orderkey 1061385

Packing unit 1 pc

Catalog page Page 143 (C-4-2019)

GTIN 4055626712895

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85363010

Country of origin DE (Germany)

Drawings

Ambient conditions

Protective circuit

Standards and Regulations

Classifications

Dimensions

General

Connection data

Environmental Product Compliance

Drawings

Dimensional drawing

Pictogram

Circuit diagram

[Back to top](#)Dimensions

Height 105.8 mm

Width 6.2 mm +0.1 mm

Depth 100 mm (incl. DIN rail 7.5 mm)

[Back to top](#)Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 %

Altitude $\leq$ 4000 m (amsl (above mean sea level))

Degree of protection IP20

[Back to top](#)General

Housing material PBT

Flammability rating according to UL 94 V-0

Color traffic grey A RAL 7042

light grey RAL 7035

Mounting type DIN rail: TH 35 - 7.5 mm

Type DIN rail module, two-section, divisible

Direction of action Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground

[Back to top](#)Protective circuit

IEC test classification C1

C2

C3

Nominal voltage UN 5 V DC

Maximum continuous voltage UC 5 V DC

3 V AC

Rated current 5 A (55 °C)

Operating effective current ICat UC $\leq$ 1 mA

Residual current IPE $\leq$ 1 μ A

Nominal discharge current $I_n(8/20)$ μ s (line-line) 0.5 kA

Nominal discharge current $I_n(8/20)$ μ s (line-earth) 5 kA

Total discharge current $I_{total}(8/20)$ μ s 10 kA

Voltage prote...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TTC-6P-3-5DC-PT-I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.