

INDUSTRIAL COMPONENT DATA

TTC-6P-3-EX-24DC-UT-I 1064665 PHOENIX CONTACT Surge protection, consisting of protective plug and base eleme..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TTC-6P-3-EX-24DC-UT-I



Manufacturer	PHOENIX CONTACT
MPN / Reference	TTC-6P-3-EX-24DC-UT-I
Catalog number	1064665
Category	Combined arrester for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-822D6FD918
Generated	2026-08-05

Product Overview

Surge protection, consisting of protective plug and base element, with integrated status indicator for a 3-wire floating Ex i signal circuit, HART-compatible.

Surge protection, consisting of plug-in protection and base element, with integrated status indication for a floating, HART-capable 3-wire intrinsically safe signal circuit.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data

Orderkey 1064665

Packing unit 1

Catalog page Page 158 (C-4-2019)

GTIN 4055626722733

Custom tariff number 85363010

Drawings

Ambient conditions

Protective circuit

Standards and Regulations

Conformity / approvals

Classifications

Dimensions

General

Connection data

General

Environmental Product Compliance

Drawings

Dimensional drawing

Pictogram

Circuit diagram

Back to topDimensions

Height 105.8 mm

Width 6.2 mm +0.1 mm

Depth 100 mm (incl. DIN rail 7.5 mm)

Back to topAmbient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 %

Altitude ≤ 2000 m (amsl (above mean sea level))

Degree of protection IP20

Back to topGeneral

Housing material PBT

Flammability rating according to UL 94 V-0

Color sky blue RAL 5015

Mounting type DIN rail: TH 35 - 7.5 mm

Type DIN rail module, two-section, divisible

Direction of action Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground

Back to topProtective circuit

IEC test classification C1

C2

C3

D1

Nominal voltage UN 24 V DC

Maximum continuous voltage UC 30 V DC

Rated current 5 A (55 °C)

Operating effective current ICat UC ≤ 5 μA

Residual current IPE ≤ 1 μA

Nominal discharge current In(8/20) μs (line-line) 0.5 kA

Nominal discharge current In(8/20) μs (line-earth) 5 kA

Pulse discharge current Iimp(10/350) μs (line-earth) 0.5 kA

Total discharge current Itotal(8/20) μs 10 kA

Voltage protection level Up(l...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TTC-6P-3-EX-24DC-UT-I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.