


INDUSTRIAL COMPONENT DATA

TVFKC 1,5/ 2-ST CP2 BD:23,24 1709653 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: TVFKC 1,5/ 2-ST CP2 BD:23,24



Manufacturer	PHOENIX CONTACT
MPN / Reference	TVFKC 1,5/ 2-ST CP2 BD:23,24
Catalog number	1709653
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-8A86906085
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 10 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Female connection, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 4, family of articles: TVFKC 1.5/.. -ST, pitch: 5 mm, connection type: Push-in spring connection, conductor connection direction/printed circuit board: 0 °, Clamping hook: - Clamping hook, plug-in system: CLASSIC COMBICON, Locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1709653

Packing unit 1

GTIN 4055626080901

Custom tariff number 85366990

Dimensions

Length [l] 23.3 mm

Width [w] 10 mm

Height [h] 15 mm

Pitch 5 mm

Dimension a 5 mm

General

Range of articles TVFKC 1,5/...-ST

Number of positions 2

Connection method Push-in spring connection

Insulating material group I

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current I_N 10 A

Nominal cross section 1.5 mm²

Flammability rating according to UL 94 V0

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Standards and Regulations

Connection in acc. with standard EN-VDE

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 5.0EC002638ETIM 6.0EC002638

UNSPSC 13.23...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TVFKC 1,5/ 2-ST CP2 BD:23,24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.