

INDUSTRIAL COMPONENT DATA

FK-MCP 1,5/10-ST-3,81BKAUBD:10 1709015 PHOENIX CONTACT PCB connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MCP 1,5/10-ST-3,81BKAUBD:10



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MCP 1,5/10-ST-3,81BKAUBD:10
Catalog number	1709015
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-74B3CEFE5F
Generated	2026-08-06

Product Overview

PCB connector

Connector for printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Gold, contact type: Female connection, Number of potentials: 10, Number of defilas: 1, Number of poles per row: 10, number of connections: 10, family of articles: FK-MCP 1.5/..-ST, pitch: 3.81mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, Stecksystm: MINI COMBICON, Locking: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1709015

Packing unit 1

GTIN 4055626033822

Custom tariff number 85366990

Item properties

Brief article description PCB connector

Plug-in system MINI COMBICON

Type of contact Female connector

Range of articles FK-MCP 1,5/..-ST

Pitch 3.81 mm
Number of positions 10
Connection method Push-in spring connection
Locking without
Number of levels 1
Number of connections 10
Number of potentials 10
Electrical parameters
Rated current 8 A
Rated insulation voltage (III/2) 160 V
Rated surge voltage (III/2) 2.5 kV
Connection capacity
Conductor cross section solid 0.14 mm² ... 1.5 mm²
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section AWG / kcmil 26 ... 16
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 0.75 mm²
Cylindrical gauge a x b / diameter 2.4 mm x 1.5 mm / -
Stripping length 9 mm
Specifications for ferrules
Recommended crimping pliers 1212034 CRIMPFOX 6
Ferrules without insulating collar, according to DIN 46228-1 Cross section: 0.25 mm²; Length: 7 mm ... 9 mm
Cross section: 0.34 mm²; Length: 7 mm ... 9 mm
Cross section: 0.5 mm²; Length: 8 mm ... 9 mm
Cross section: 0.75 mm²; Length: 8 mm ... 9 mm
Cross section: 1 mm²; Length: 8 mm ... 9 mm
Cross section: 1.5 mm²; Length: 8 mm ... 9 mm
Material data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact mater...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MCP 1,5/10-ST-3,81BKAUBD:10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.