


INDUSTRIAL COMPONENT DATA

TVFKC 1,5/ 4-ST 35 2CPBD:1.4SO 1085847 PHOENIX CONTACT Connector for printed circuit board, voltage and size..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TVFKC 1,5/ 4-ST 35 2CPBD:1.4SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	TVFKC 1,5/ 4-ST 35 2CPBD:1.4SO
Catalog number	1085847
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-9EA6BA2311
Generated	2026-08-05

Product Overview

Connector for printed circuit board, voltage and sizing (III/2): 320 V, number of poles: 4, pitch: 5 mm, connection type: spring clamp push-in, color: light grey, surface contacts: Tin

Connector for printed circuit board, nominal section: 1.5 mm², color: bright gray, nominal current: 10 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of rows: 1, number of poles: 4, family of articles: TVFKC 1.5/.. -ST, pitch: 5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

Conductive plate connector, nominal cross-section: 1.5 mm², colour: light grey, nominal current: 10 A, reference voltage (III/2): 320 V, contact surface: Sn, contact type: Female connector, number of rows: 1, number of poles: 4, item range: TVFKC 1.5/.. -ST, pitch: 5 mm, connection type: Push-in spring connection, conductor/PCB plugging direction: 0°, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2.5, locking: without, fastening type: without, packaging type: packed in a carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical characteristicsProduct PropertiesProduct Type Conductive Plate Connector
Product range TVFKC 1,5/.. -ST

Product Line COMBICON Connectors M

Number of poles 4

Steps 5 mm

Number of rows 1

Data Management Status

Revision of the article 00

Electrical propertiesRated Current IN 10 A

Rated voltage UN 320 V

Contact resistance 1.3 mΩ

Reference voltage (III/3) 250 V

Rated Shock Resistance Voltage (III/3) 4 kV

Rated Voltage (III/2) 320 V

Rated Shock Withstand Voltage (III/2) 4 kV

Reference voltage (II/2) 630 V

Rated Shock Withstand Voltage (II/2) 4 kV

Connection featuresConnection technology

Type Standard

Connector System COMBICON MSTB 2,5

Nominal cross-section 1.5 mm²

Contact Type Female connector

Locking

Lock Mode without

Mounting Flange without

Conductor connection

Connection type Push-in spring connection

Conductor/PCB Plugging Direction 0 °

Rigid conductor cross-section 0.2 mm² ... 1.5 mm²

Soft conductor section 0.2 mm² ... 1.5 mm²

Conductive section. AWG 24 ... 16

Soft conductor section with end cap, without plastic bushing 0.25 mm² ... 1.5 mm² (only in connection with CRIMPFOX 6)

Soft conductor section with plastic end cap and socket 0.25 mm² ... 1.5 mm² (only in connection with CRIMPFOX 6)

Template a x b / diameter 2.4 mm x 1.5 mm / 1.9 mm

Stripping length 8 mm

Data for Bits Without Insulating Collar

Recommended crimping tool 1212034 CRIMPFOX 6

Data for Bits with Insulating Collar

Recommended crimping tool 1212034 CRIMPFOX 6

Material GuidanceMaterial indication - cont...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TVFKC 1,5/ 4-ST 35 2CPBD:1.4SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.