

INDUSTRIAL COMPONENT DATA

SAC-3P-M12MS/5,0-PUR/M12FR2LBK 1555457 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MS/5,0-PUR/M12FR2LBK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MS/5,0-PUR/M12FR2LBK
Catalog number	1555457
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-1C826074EC
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 3-pole, PUR/PVC, grayish black RAL 7021, Straight male connector M12, coding: A, to Elbow connection female M12, coding: A, with 2 LEDs, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Key Commercial Data

Orderkey 1555457

Packing unit 5 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356165617

Weight per Piece (excluding packing) 202.200 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 5 m

Ambient conditions

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 24 V

24 V DC

Number of positions 3

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Status display 2 LEDs

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR/PVC black

Cable type (abbreviation) 350

Cable abbreviation LiYY-11Y

UL AWM style 20549 / 1729

Conductor cross section 0.34 mm^2

Conductor structure signal line $42 \times 0.10 \text{ mm}$

Core diameter including insulation $1.5 \text{ mm} \pm 0.05 \text{ mm}$

Thickness, insulation $\geq 0.23 \text{ mm}$ (Core insulation)

Wire colors brown, blue, black

Overall twist 3 wires, twisted

Length of twist, overall twist 55 mm

External sheath, color black-gray RAL 7021

Inner sheath thickness approx. 0.5 mm

Outer sheath thickness $\geq 0.38 \text{ mm}$ (Outer cable sheath)

External cable diameter D $5.2 \text{ mm} \pm 0.2 \text{ mm}$

Smallest bending radius, f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MS/5,0-PUR/M12FR2LBK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.