

INDUSTRIAL COMPONENT DATA

SAC-4P-MS/ 2,0-100/FS SCO OBS 1562699 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-MS/ 2,0-100/FS SCO OBS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-MS/ 2,0-100/FS SCO OBS
Catalog number	1562699
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-178BDB4C57
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 4-pole, halogen-free PUR, grey RAL 7001, M12 SPEEDCON straight male connector, coding: A, to M12 SPEEDCON straight connection female, coding: A, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1562699

Packing unit 5 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356298513

Weight per Piece (excluding packing) 106.020 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 3 m

Ambient conditions

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 250 V AC

250 V DC

Number of positions 4

Insulation resistance $\geq 10 \text{ M}\Omega$

Coding A - standard

Status display No

Overvoltage category II

Degree of pollution 3

Torque 0.4 Nm

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR/PVC gray

Cable type (abbreviation) 100

Cable abbreviation LiYY-11Y

Conductor cross section 0.34 mm²

AWG signal line 22

Conductor structure signal line 42x 0.10 mm

Core diameter including insulation 1.5 mm $\pm 0.05 \text{ mm}$

Thickness, insulation $\geq 0.3 \text{ mm}$ (Core insulation)

$\geq 0.38 \text{ mm}$ (Outer cable sheath)

approx. 0.35 mm (Inner sheath)

Wire colors brown, white, blue, black

Overall twist 4 wires, twisted

External sheath, color gray RAL 7001

External cable diameter D 5.2 mm $\pm 0.2 \text{ mm}$

Smallest bending radius, fixed installation 52 mm

Smallest bending radius, movable installation 52 mm

Number of bending c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-MS/ 2,0-100/FS SCO OBS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.