

INDUSTRIAL COMPONENT DATA

TW 50/ 1-CL 1708744 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: TW 50/ 1-CL



Manufacturer	PHOENIX CONTACT
MPN / Reference	TW 50/ 1-CL
Catalog number	1708744
Category	Panel feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-960F9EEF69
Generated	2026-08-05

Product Overview

Panel feed-through terminal block

Wall terminal block, connection type: T-LOX articulated lever connection, Terminal connection, number of poles: 1, charging current: 150 A, cross-section: 10 mm² - 50 mm², conductor connection direction with respect to the plug direction: 0 °, width: 38 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1708744

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4055626020310

Weight per Piece (excluding packing) 168.000 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Nominal cross section 50 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Insulating material group I

Nominal current I_N 150 A

Maximum load current 150 A

Nominal voltage U_N 1000 V

Number of positions 1

Dimensions

Width 38 mm

Pitch 20 mm

Plate thickness 1 mm ... 5 mm

Connection data

Connection side outside

Connection method T-LOX knee lever connection

Note Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area.

Conductor cross section solid min. 10 mm²

Conductor cross section solid max. 50 mm²

Conductor cross section flexible min. 16 mm²

Conductor cross section flexible max. 50 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 10 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 50 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 10 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 50 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 6 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 16 mm²

St...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TW 50/ 1-CL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.