

INDUSTRIAL COMPONENT DATA

TW 95/ 6-CL 1708757 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: TW 95/ 6-CL



Manufacturer	PHOENIX CONTACT
MPN / Reference	TW 95/ 6-CL
Catalog number	1708757
Category	Panel feed-through terminal block
Minimum order	5 Pcs
Document ID	EO-C8EC7B1ED2
Generated	2026-08-04

Product Overview

Panel feed-through terminal block

Terminal block, connection type: T-LOX articulated lever connection, Terminal connection, number of poles: 6, charging current: 232 A, conductor connection direction with respect to the plug direction: 0 °, width: 175 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1708757

Packing unit 5 pc

Minimum order quantity 5 pc

Note Made to Order (non-returnable)

GTIN 4055626020426

Weight per Piece (excluding packing) 1,272.000 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 6

Nominal cross section 95 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Degree of pollution 3

Overvoltage category III

Insulating material group I

Connection in acc. with standard IEC 60947-7-1

Nominal current I_N 232 A

Maximum load current 232 A

Nominal voltage U_N 1000 V

Open side panel No

Number of positions 6

Dimensions

Width 175 mm

Length 120.05 mm

Pitch 25 mm

Plate thickness 1 mm ... 5 mm

Connection data

Connection side outside

Connection method T-LOX knee lever connection

Note Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area.

Conductor cross section solid min. 25 mm²

Conductor cross section solid max. 95 mm²

Conductor cross section flexible min. 25 mm²

Conductor cross section flexible max. 95 mm²

Conductor cross section AWG min. 4

Conductor cross section AWG max. 3/0

Conductor cross section flexible, with ferrule without plastic sleeve min. 25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 95 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TW 95/ 6-CL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.