

INDUSTRIAL COMPONENT DATA

SD FLASH 512MB MODULAR MUX 2701872 PHOENIX CONTACT

Two of these SD cards, with two ILC 131 ETHs and the indi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SD FLASH 512MB MODULAR MUX



Manufacturer	PHOENIX CONTACT
MPN / Reference	SD FLASH 512MB MODULAR MUX
Catalog number	2701872
Category	PLC memory card
Minimum order	1 Pcs
Document ID	EO-19E09191EE
Generated	2026-08-06

Product Overview

Two of these SD cards, with two ILC 131 ETHs and the individually required input and output terminals, form a multiplexer system that requires no programming. Easy configuration via a small number of wire jumpers. Wireless, Ethernet cable or network connection.

Two of these SD cards convert the two ILC 131 ETH and the necessary input and output terminals into a multiplexer system without the need for programming. Easy setup thanks to the few cable jumpers. Connection via radio, Ethernet cable or network.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Control Systems (CST)
--------------	---

Additional Product Information

Product description

The basic function of the SD FLASH 512MB MODULAR MUX is aimed at those who wish to utilize the advantages of a flexible multiplexer solution without having to program controllers. To enable this, the required minimum configuration is implemented via a small number of wire jumpers. Standard components (2 x ILC 131 ETH; 2 x SD FLASH 512MB MODULAR MUX) are used for this. The necessary input and output terminals are also used. Communication between the two multiplexer components (ILC 131 ETH) is then established fully automatically via an Ethernet cable or a transparent wireless transmission.

The two multiplexers can be integrated into an Ethernet network as an option. The required Ethernet configuration is

implemented via the web interface of the ILC 131 ETH. This can be done simply using a PC and a standard browser.

The following standard components are required:

2 x ILC 131 ETH (Order No. 2700973)

2 x SD FLASH 512MB MODULAR MUX (Order No. 2701872)

To connect the two systems, an Ethernet cable (wired communication) or

1 x FL BT EPA AIR SET (Order No. 2693091) (wireless communication) is required.

The specified number of input and output terminals from the Inline Modular range from Phoenix Contact (marked with logo, see below) is also required.

All wireless systems that can transmit TCT/IP data transparently can be used to connect the ILC 131 ETH to a multiplexer system.

The following Phoenix Contact wireless products are suitable for this:

1 x FL BT EPA AIR...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SD FLASH 512MB MODULAR MUX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.