

INDUSTRIAL COMPONENT DATA

BLT-T2-1S-320-UT 2906101 PHOENIX CONTACT Type 2 surge arrester

Brand: PHOENIX CONTACT | Manufacturer Part Number: BLT-T2-1S-320-UT



Manufacturer	PHOENIX CONTACT
MPN / Reference	BLT-T2-1S-320-UT
Catalog number	2906101
Category	Surge protection device for power supply systems
Minimum order	10 Pcs
Document ID	EO-C27C12D716
Generated	2026-08-05

Product Overview

Type 2 surge arrester

Type 2 surge arrester for universal mounting on lights, cable junction boxes, installation boxes, wall channels, underfloor installations or directly on terminal equipment. Special for insulation protection class I with optical defect notification. Installation in branch or pass-through wiring. Construction: 230 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2906101

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 69 (C-4-2017)

GTIN 4055626058085

Weight per Piece (excluding packing) 44.840 g

Custom tariff number 85363030

Country of origin CN (China)

Dimensions

Height 56 mm

Width 36.5 mm

Depth 34 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 80 °C

Ambient temperature (storage/transport) -40 °C ... 80 °C

Altitude ≤ 2000 m (amsl (above mean sea level))

Permissible humidity (operation) 5 % ... 95 %

General

IEC test classification II / III

T2 / T3

EN type T2 / T3

IEC power supply system TN-S

TT

Mode of protection L-N

L-PE

N-PE

Mounting type 4 mm screw

Color light grey RAL 7035

Housing material PA 6.6

Degree of pollution 2

Flammability rating according to UL 94 V-0

Protection class I

Type Installation module

Surge protection fault message optical

Protective circuit

Nominal voltage UN 100 V AC ... 277 V AC (TN-S)

100 V AC ... 277 V AC (TT)

Nominal frequency fN 50 Hz (60 Hz)

Maximum continuous operating voltage UC(L-N) 320 V AC

Maximum continuous operating voltage UC(L-PE) 305 V AC

Maximum continuous voltage UC(N-PE) 305 V AC

Rated load current IL 16 A

Residual current IPE ≤ 5 μA

Nominal discharge current $I_n(8/20)$ μs (L-N) 5 kA

Nominal discharge current $I_n(8/20)$ μs (L-PE) 5 kA

Nominal discharge current $I_n(8/20)$ μs (N-PE) 10 kA

Maximum discharge current $I_{max}(8/20)$ μs (L-N) 10 kA

Maximum discharge current $I_{max}(8/20)$ μs (L-PE) 10 kA

Maximum discharge...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BLT-T2-1S-320-UT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.