

**INDUSTRIAL COMPONENT DATA**

# UBE/D (60X10) 0803719 PHOENIX CONTACT Marker carriers

Brand: PHOENIX CONTACT | Manufacturer Part Number: UBE/D (60X10)



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | UBE/D (60X10)                   |
| Catalog number  | 0803719                         |
| Category        | Mounting for labelling material |
| Minimum order   | 50 Pcs                          |
| Document ID     | EO-10EA6A99DC                   |
| Generated       | 2026-08-02                      |

## Product Overview

Marker carriers

Support for indexes for terminal strips, for the identification of terminal groups, for mounting on the NS 32 or NS 35/7.5 terminal strip, callout size: 60 x 10 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; MS Material

## Additional Product Information

Key Commercial Data

Orderkey 0803719

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 587 (C-3-2017)

GTIN 4055626146263

Weight per Piece (excluding packing) 8.040 g

Custom tariff number 39269097

Country of origin DE (Germany)

Dimensions

Length (b) 48.5 mm

Width (a) 10 mm

Height (c) 60 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

General

Color gray

Base element material PA

Components free from silicone and halogen

Flammability rating according to UL 94 V0

Material PA

RoHS compliant Yes

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type DIN rail mounting

Result Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

Class I 2

Class F 2

Surface flammability (ASTM E 162) passed

Specific optical density of smoke (ASTM E 662) passed

Smoke gas toxicity (SMP 800C) passed

Heat dissipation calorimetric (ASTM E 1354) 28 MJ/kg

R22 HL 1 - HL 3

R23 HL 1 - HL 3

R24 HL 1 - HL 3

R26 HL 1 - HL 3

Standards and Regulations

Flammability rating according to UL 94 V0

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Classi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UBE/D (60X10) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.