

INDUSTRIAL COMPONENT DATA

UC-WMTBA (24X5)/PP SR 1199630 PHOENIX CONTACT Cable marker, Mat, silver, unlabelled, labelable with: TOPMARK..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-WMTBA (24X5)/PP SR



Manufacturer	PHOENIX CONTACT
MPN / Reference	UC-WMTBA (24X5)/PP SR
Catalog number	1199630
Category	Cable coding system
Minimum order	10 Pcs
Document ID	EO-18C4003A89
Generated	2026-08-05

Product Overview

Cable marker, Mat, silver, unlabelled, labelable with: TOPMARK NEO, TOPMARK LASER, mounting class: Mounting with cable tie, cable diameter: > 4 mm, Number of individual indexes: 12, text field height: 5 mm, text field width: 24 mm

Cable marker, Mat, silver, unlabeled, labelable with: TOPMARK NEO, TOPMARK LASER, mounting class: Mounting with cable ties, cable diameter: > 4 mm, usable surface: 24 x 5 mm, Number of individual indexes: 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > MS Material

Additional Product Information

ETIM for 1199630 Cable terminations and insulation products (EC001530)

Feature Name

Feature Value

Model (EF000010)

Card shape

Type (EF001139)

Medium-walled

Tooththing (EF009649)

None

Material (EF002169)

Other

Cable diameter (EF002356)

136 mm
Length (EF001438)
10.618802 mm
Width (EF000008)
24 mm
Colour (EF000007)
Silver
Fluorescent (EF009518)
No
With label space (EF003456)
Yes
Mounting method (EF000003)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-WMTBA (24X5)/PP SR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.