

INDUSTRIAL COMPONENT DATA

UC-WMTBA (29X8)/PP YE CUS 1541711 PHOENIX CONTACT

Cable marker, available: matted, yellow, labelled according to customer specifications

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-WMTBA (29X8)/PP YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UC-WMTBA (29X8)/PP YE CUS
Catalog number	1541711
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-59435B334B
Generated	2026-08-03

Product Overview

Cable marker, available: matted, yellow, labelled according to customer specifications, mounting class: Mounting with cable tie, cable diameter: > 6 mm, usable area: 29 x 8 mm, Number of individual indexes: 12

Cable Marker

Cable marker, can be ordered: by sheet, yellow, labeled according to customer specifications, mounting type: Assembly with cable ties, cable diameter: > 6 mm, lettering field size: 29 x 8 mm, Number of individual labels: 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking

Type Card form

Marking

Number of individual labels 12

Number of individual labels per row 4

Identification technology Direct laser marking

DimensionsWidth 13.5 mm

Length 29 mm

External dimensions

Outside diameter > 6 mm ... 136 mm

Material specificationsColor yellow

Material PP

Components free from silicone and halogen

Cable/line External cable diameter > 6 mm

Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish

Result Test passed

Test for substances that would hinder coating with paint or varnish

Result Test passed

Scratch test for the determining scratch resistance

Specification DIN EN ISO 1518-1:2019-10 (following)

Requirements ≥ 5 N

Result Test passed

Tesafilm test

Specification DIN EN ISO 2409:2013 (following)

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03

Result Test passed

Test duration 96 h

Specification IEC 60068-2-2:2007-07

Result Test passed

Duration 96 h

Maximum temperature +85 °C

Temperature resistance

Specification ANSI/UL 969-2018:03 (following)

Test duration 240 h

Rating 125 °C (150 °C) Test passed

Specification ISO 175:2010 (following)

Test duration 168 h

Diesel

[CAS No. 68476-34-6] Test passed

IRM 901 Test passed

IRM 902 Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification DIN 50018:2013-05

Result Test passed

Climate level AHT 1.0 S

Cycles 2

Salt spray test

Specification DIN E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-WMTBA (29X8)/PP YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.