

INDUSTRIAL COMPONENT DATA

UCS 125-87-F-GD-RPI 7035 1019724 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS 125-87-F-GD-RPI 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS 125-87-F-GD-RPI 7035
Catalog number	1019724
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-37E070BE16
Generated	2026-08-03

Product Overview

Electronic housing

Complete housing for printed circuit boards. It includes the halves of the case, side walls with holes for all relevant connections, adhesive brackets for fixing the Raspberry Pi model B2 and B3 computer, screws for the case and fixing the board; Light grey housing colour with turquoise blue angular inserts

Complete housing for printed-circuit boards. Includes housing half shells, side panels with openings for all relevant connections, adhesive pads for affixing the Raspberry Pi model B2 and B3 computers, screws for housing and PCB attachment; light gray housing with turquoise-blue corner inlays

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note The housing can be opened a maximum of 10 times.

Note on application Attach the adhesive pads: Make sure that the surface of the housing is clean, dry, and free of grease.

Temperature range: +18°C ... +30°C / Closing pressure force: 60 N / Closing pressure time: 3 s

Product propertiesProduct type Complete housing

Housing type Universal housings

Housing series UCS

Product family UCS 125-87

Type Flat design (GD), RPI

Ventilation openings present no

Data management status

Article revision 00

DimensionsDimensional drawing

Width 125 mm

Height 87 mm

Depth 47 mm

Dimensions 100 mm x 62 mm (Maximum circuit board dimensions)

PCB design

PCB thickness 0.8 mm ... 3 mm

Material specificationsColor (Housing) light gray (RAL 7035)

Flammability rating according to UL 94 V0

CTI according to IEC 60112 225

Insulating material PC

Housing material PC

Surface characteristics untreated

Environmental and real-life conditionsPower dissipation single housing for 20 °C

Ambient temperature 20 °C

Reduction factor 1

Mounting position vertical

Power dissipation 9.7 W

Power dissipation single housing for 30 °C

Ambient temperature 30 °C

Reduction factor 0.85

Mounting position vertical

Power dissipation 8.3 W

Power dissipation single housing for 40 °C

Ambient temperature 40 °C

Reduction factor 0.68

Mounting position vertical

Power dissipation 6.5 W

Power dissipation single housing for 50 °C

Ambient temperature 50 °C

Reduction factor 0.55

Mounting position vertical

Power dissip...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS 125-87-F-GD-RPI 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.