

INDUSTRIAL COMPONENT DATA

UCS 145-125-F-GD-RPI 9005 1019720 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS 145-125-F-GD-RPI 9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS 145-125-F-GD-RPI 9005
Catalog number	1019720
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-E26D874D65
Generated	2026-08-05

Product Overview

Electronic housing

Complete housing for printed circuit boards. It includes the case halves, side walls with holes for all relevant connections, adhesion domes for fixing the Raspberry Pi B2 and B3 computer, screws for the case and fixing the board; Black housing color with turquoise blue angular inserts

Complete housing for printed-circuit boards. Includes housing half shells, side panels with openings for all relevant connections, adhesive pads for affixing the Raspberry Pi model B2 and B3 computers, screws for housing and PCB attachment; black housing with turquoise blue corner inlays

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note The housing can be opened a maximum of 10 times.

Note on application Attach the adhesive pads: Make sure that the surface of the housing is clean, dry, and free of grease.

Temperature range: +18°C ... +30°C / Closing pressure force: 60 N / Closing pressure time: 3 s

General Refer to the data sheet for the range in the download area.

Product propertiesProduct type Complete housing

Housing type Universal housings

Housing series UCS

Product family UCS 145-125

Type Flat design (GD), RPI

Ventilation openings present no
Data management status
Article revision 00
DimensionsDimensional drawing
Width 145 mm
Height 125 mm
Depth 47 mm
Dimensions 120 mm x 100 mm (Maximum circuit board dimensions)
PCB design
PCB thickness 0.8 mm ... 3 mm
Material specificationsColor (Housing) black (RAL 9005)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 225
Insulating material PC
Housing material PC
Surface characteristics untreated
Environmental and real-life conditionsPower dissipation single housing for 20 °C
Ambient temperature 20 °C
Reduction factor 1
Mounting position vertical
Power dissipation 11 W
Power dissipation single housing for 30 °C
Ambient temperature 30 °C
Reduction factor 0.85
Mounting position vertical
Power dissipation 9.4 W
Power dissipation single housing for 40 °C
Ambient temperature 40 °C
Reduction factor 0.7
Mounting position vertical
Power dissipation 7.7 W
Power dissipation single housing for 50 °C
Ambient temperature 50....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS 145-125-F-GD-RPI 9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.