

INDUSTRIAL COMPONENT DATA

UCS 195-145-F-GD 7035 2203336 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS 195-145-F-GD 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS 195-145-F-GD 7035
Catalog number	2203336
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-149363EB82
Generated	2026-08-06

Product Overview

Electronic housing

Complete housing for printed circuit boards, flexible positioning; includes the halves of the housing, closed side walls, adhesion domes for fixing the plate, screws for housing and fixing the plate; light grey housing colour with turquoise blue angular inserts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

Additional Product Information

Key Commercial Data

Orderkey 2203336

Packing unit 1 pc

GTIN 4055626404486

Weight per Piece (excluding packing) 600.900 g

Custom tariff number 85389099

Country of origin DE (Germany)

Item properties

Type UCS 195-145-F-GD 7035

Order No. 2203336

Housing type Universal housings

Type flat

Measurements

Dimensional drawing

Width [w] 195 mm

Height [h] 145 mm

Depth [d] 47 mm

Dimensions 170 mm x 120 mm (Maximum circuit board dimensions)

Material specifications

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material PC

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

PCB data

Number of PCB holders 1

Note on PCB holders This product is prepared for a printed-circuit board. Additional printed-circuit boards can be mounted using adhesive pads (accessories).

PCB thickness 0.8 mm ... 3 mm

Total PCB surface 14400 mm²

Type of PCB mount Bolt mounting

Power dissipation, single housing at 20°C

Ambient temperature 20 °C

Reduction factor 1

Mounting position vertical

Power dissipation 19 W

Power dissipation, single housing at 30 °C

Ambient temperature 30 °C

Reduction factor 0.83

Mounting position vertical

Power dissipation 15.7 W

Power dissipation, single housing at 40 °C

Ambient temperature 40 °C

Reduction factor 0.66

Mounting position vertical

Power dissipation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS 195-145-F-GD 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.