

INDUSTRIAL COMPONENT DATA

UCS DIN 125-H 7035 2203841 PHOENIX CONTACT DIN rail adapter for mounting one UCS 125-87-H housing (long side..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS DIN 125-H 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS DIN 125-H 7035
Catalog number	2203841
Category	DIN-rail adapter
Minimum order	1 Pcs
Document ID	EO-36E51745D3
Generated	2026-08-06

Product Overview

DIN rail adapter for mounting one UCS 125-87-H housing (long side) or UCS 145-125-H housing (short side) onto an NS 35 DIN rail; will be set into the housing instead of a UCS SW 125 side wall; material: polycarbonate; color: light gray, similar to RAL 7035

Rail adapter for mounting a UCS 125-87-H (long side) or UCS 145-125-H (short side) housing on a DIN NS 35 rail, it is placed in the housing instead of a UCS SW 125 side wall, material: polycarbonate, color: light gray similar to RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data

Orderkey 2203841

Packing unit 1 pc

GTIN 4055626540337

Weight per Piece (excluding packing) 20.000 g

Custom tariff number 39269097

Country of origin DE (Germany)

Item properties

Material specifications

General information

Standards and regulations

Measurements

Ambient conditions

Packaging information

Classifications

Item properties

Type UCS DIN 125-H 7035

Order No. 2203841

Type high

[Back to top](#)Measurements

Width [w] 59.4 mm

Height [h] 96 mm

Depth [d] 16.9 mm

[Back to top](#)Material specifications

Color (RAL) light gray (7035)

Insulating material PC

Flammability rating according to UL 94 V0

Housing material PC

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)

[Back to top](#)General information

Note Observe the notes in the data sheet.

[Back to top](#)Packaging information

Pieces per package 1

Denomination packing units Pcs.

[Back to top](#)Standards and regulations

Flammability rating according to UL 94 V0

[Back to top](#)Classifications

eCl@ss

eCl@ss 5.0 27370400

eCl@ss 5.1 27370400

eCl@ss 6.0 27370400

eCl@ss 7.0 27370419

eCl@ss 8.0 27370419

eCl@ss 9.0 27370419

[Back to top](#)ETIM

ETIM 5.0 EC001024

ETIM 6.0 EC001024

ETIM 7.0 EC001024

[Back to top](#)

ETIM for 2203841 Low-voltage industrial controls and switchgear (EC001024)

Feature Name

Feature Value

Type of fastening (EF002442)

Other

Material (EF002169)

Plastic

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS DIN 125-H 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.