

INDUSTRIAL COMPONENT DATA

UCS DIN 145-H 7035 2203840 PHOENIX CONTACT DIN rail adapter for mounting one UCS 145-125-H housing (long sid..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS DIN 145-H 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS DIN 145-H 7035
Catalog number	2203840
Category	DIN-rail adapter
Minimum order	1 Pcs
Document ID	EO-0F1763DC80
Generated	2026-08-05

Product Overview

DIN rail adapter for mounting one UCS 145-125-H housing (long side) or UCS 195-145-H housing (short side) onto an NS 35 DIN rail; will be set into the housing instead of a UCS SW 145 side wall; material: polycarbonate; color: light gray, similar to RAL 7035

Rail adapter for mounting a UCS 145-125-H (long side) or UCS 195-145-H (short side) housing on a DIN NS 35 rail, it is placed in the housing instead of a UCS SW 145 sidewall, material: polycarbonate, color: light gray similar to RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2203840

Packing unit 1 pc

GTIN 4055626540320

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 39269097

Country of origin DE (Germany)

Item properties

Material specifications

General information

Standards and regulations

Measurements[Ambient conditions](#)[Packaging information](#)[Classifications](#)[Item properties](#)[Type UCS DIN 145-H 7035](#)[Order No. 2203840](#)[Housing type Universal housings](#)[Type high](#)[Back to topMeasurements](#)[Width \[w \] 59.4 mm](#)[Height \[h \] 116 mm](#)[Depth \[d \] 16.9 mm](#)[Back to topMaterial specifications](#)[Color \(RAL\) light gray \(7035\)](#)[Insulating material PC](#)[Flammability rating according to UL 94 V0](#)[Housing material PC](#)[Back to topAmbient conditions](#)[Ambient temperature \(storage/transport\) -40 °C ... 70 °C](#)[Ambient temperature \(assembly\) -5 °C ... 100 °C](#)[Ambient temperature \(operation\) -40 °C ... 100 °C \(depending on power dissipation\)](#)[Back to topGeneral information](#)[Note Observe the notes in the data sheet.](#)[Back to topPackaging information](#)[Pieces per package 1](#)[Denomination packing units Pcs.](#)[Back to topStandards and regulations](#)[Flammability rating according to UL 94 V0](#)[Back to topClassifications](#)[eCl@ss](#)[eCl@ss 5.0 27370400](#)[eCl@ss 5.1 27370400](#)[eCl@ss 6.0 27370400](#)[eCl@ss 7.0 27370419](#)[eCl@ss 8.0 27370419](#)[eCl@ss 9.0 27370419](#)[Back to topETIM](#)[ETIM 5.0 EC001024](#)[ETIM 6.0 EC001024](#)[ETIM 7.0 EC001024](#)[Back to top](#)[ETIM for 2203840 Low-voltage industrial controls and switchgear \(EC001024\)](#)[Feature Name](#)[Feature Value](#)[Type of fastening \(EF002442\)](#)[Other....](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS DIN 145-H 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.