


## INDUSTRIAL COMPONENT DATA

# UCS PED 7035 2203392 PHOENIX CONTACT Stand for mounting the UCS housing height: 47 mm material: polyamide CO..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS PED 7035



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | UCS PED 7035                     |
| Catalog number  | 2203392                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-8FBD668FAA                    |
| Generated       | 2026-08-04                       |

## Product Overview

Stand for mounting the UCS housing; height: 47 mm; material: polyamide; color: light gray, similar to RAL 7035; wall mounting option is integrated, snaps into the screw holes of the housing

Foot for attaching UCS housings, height: 47 mm, material: polyamide, color: light gray, similar to RAL 7035, integrated wall mounting option, snaps into threaded holes in the housing

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

General The UCS PED... stand has drill holes that are also suitable for wall mounting.

Recommended screws for wall mounting: S5 dowel, screw  $\varnothing$  4.0 mm.

Product propertiesProduct type Mounting material

Housing type Universal housings

Housing series UCS

Ventilation openings present no

Data management status

Article revision 02

DimensionsWidth 90 mm

Height 37.5 mm  
Depth 19.2 mm  
Diameter mounting hole 4 mm  
Material specificationsColor (Housing) light gray (RAL 7035)  
Flammability rating according to UL 94 V0  
CTI according to IEC 60112 600  
Insulating material PA  
Housing material Polyamide  
Surface characteristics untreated  
Environmental and real-life conditionsAmbient conditions  
Max. IP code to attain IP40  
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)  
Ambient temperature (storage/transport) -40 °C ... 55 °C  
Ambient temperature (assembly) -5 °C ... 100 °C  
Relative humidity (storage/transport) 80 %  
MountingMounting type Snap in  
Mounting position Wall mounting  
Packaging specificationsType of packaging PE bag  
ETIM for 2203392 Low-voltage industrial controls and switchgear (EC002779)  
Feature Name  
Feature Value  
Type of enclosure (EF003086)  
Open  
Housing connectable (EF003088)  
No  
Suitable for rail mounting (EF003972)  
No  
Wall mounting possible (EF003973)  
No  
With integrated PCB-mounting connection system (EF003087)  
No  
Material (EF002169)  
Other  
Surface finishing (EF...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS PED 7035 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.