

INDUSTRIAL COMPONENT DATA

UCS PED 9005 2203393 PHOENIX CONTACT Stand for mounting the UCS housing height: 47 mm material: polyamide CO..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS PED 9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS PED 9005
Catalog number	2203393
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-2160A92FE6
Generated	2026-08-05

Product Overview

Stand for mounting the UCS housing; height: 47 mm; material: polyamide; color: black, similar to RAL 9005; wall mounting option is integrated, snaps into the screw holes of the housing

UCS housing stand, height: 47 mm, material: polyamide, color: black, similar to RAL 9005, integrated wall mounting option, snaps into the threaded holes of the housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

General The UCS PED... stand has drill holes that are also suitable for wall mounting.

Recommended screws for wall mounting: S5 dowel, screw $\varnothing$ 4.0 mm.

Product propertiesProduct type Mounting material

Housing type Universal housings

Housing series UCS

Ventilation openings present no

Data management status

Article revision 02

DimensionsWidth 90 mm

Height 37.5 mm
Depth 19.2 mm
Diameter mounting hole 4 mm
Material specificationsColor (Housing) black (RAL 9005)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Insulating material PA
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP40
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Relative humidity (storage/transport) 80 %
MountingMounting type Snap in
Mounting position Wall mounting
Packaging specificationsType of packaging PE bag
ETIM for 2203393 Low-voltage industrial controls and switchgear (EC002779)
Feature Name
Feature Value
Type of enclosure (EF003086)
Open
Housing connectable (EF003088)
No
Suitable for rail mounting (EF003972)
No
Wall mounting possible (EF003973)
No
With integrated PCB-mounting connection system (EF003087)
No
Material (EF002169)
Other
Surface finishing (EF00656...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS PED 9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.