

INDUSTRIAL COMPONENT DATA

UCS SW 125-F AL 2203366 PHOENIX CONTACT Side panel for use with housing half shells 125 x 87 mm and 145 x 12..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS SW 125-F AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS SW 125-F AL
Catalog number	2203366
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-4B661B0888
Generated	2026-08-04

Product Overview

Side panel for use with housing half shells 125 x 87 mm and 145 x 125 mm in size; panel thickness: 2 mm; total height of housing: 47 mm; material: aluminum

Sidewall for use with housing halves in sizes 125 x 87 mm and 145 x 125 mm; wall thickness 2 mm; total housing height 47 mm; Material: Aluminum

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2203366

Packing unit 1

GTIN 4055626459462

Custom tariff number 76169990

Item properties

Material specifications

Mechanical strength/tumbling barrel

Packaging information

Measurements

Ambient conditions

Test for substances that would hinder coating with paint or varnish

Classifications

Item properties

Type UCS SW 125-F AL

Order No. 2203366

Housing type Universal housings

Type flat

Back to topMeasurements

Width [w] 96 mm

Height [h] 39.5 mm

Depth [d] 2 mm

Back to topMaterial specifications

Color (RAL) aluminum color

Housing material Aluminum

Back to topAmbient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)

Back to topMechanical strength/tumbling barrel

Specification IEC 60068-2-31:2008-05

Height of fall 50 cm

Number of drop cycles 50

Back to topTest for substances that would hinder coating with paint or varnish

Result Test passed

Specification VW PV 3.10.7:2005-02

Back to topPackaging information

Pieces per package 10

Denomination packing units Pcs.

Back to topClassifications

eCl@ss

eCl@ss 5.1 27180506

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

Back to topETIM

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

Back to top

ETIM for 2203366 Low-voltage industrial controls and switchgear (EC002779)

Feature Name

Feature Value

Type of enclosure (EF003086)

Open...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS SW 125-F AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.