

INDUSTRIAL COMPONENT DATA

UCS SW 145-H 7035 2203375 PHOENIX CONTACT Side panel

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS SW 145-H 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS SW 145-H 7035
Catalog number	2203375
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-D453FC5C32
Generated	2026-08-03

Product Overview

Side panel

Sidewall for use with housing halves in sizes 195 x 145 mm and 145 x 125 mm; wall thickness 2 mm; total housing height 67 mm; polycarbonate material; light grey colour similar to RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2203375

Packing unit 10 pc

GTIN 4055626427607

Weight per Piece (excluding packing) 8.170 g

Custom tariff number 85389099

Country of origin DE (Germany)

Item properties

Type UCS SW 145-H 7035

Order No. 2203375

Housing type Universal housings

Type high

Measurements

Width [w] 116 mm

Height [h] 59.5 mm

Depth [d] 2 mm

Material specifications

Color (RAL) light gray (7035)

Insulating material PC

CTI according to IEC 60112 2

Flammability rating according to UL 94 V0

Housing material PC

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)

Mechanical strength/tumbling barrel

Specification IEC 60068-2-31:2008-05

Height of fall 50 cm

Number of drop cycles 50

Thermostability (ball thrust test)

Specification IEC 60695-10-2:2014-02

Temperature 125 °C

Test duration 1 h

Force 20 N

Test for assessing the risk of fire (glow wire)

Specification DIN EN 60695-2-11 (VDE 0471-2-11):2014-11

Temperature 850 °C

Time of exposure 30 s

Test for substances that would hinder coating with paint or varnish

Result Test passed

Specification VW PV 3.10.7:2005-02

Packaging information

Pieces per package 10

Denomination packing units Pcs.

Standards and regulations

Flammability rating according to UL 94 V0

Classifications

eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 5.0EC001031E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS SW 145-H 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.