

INDUSTRIAL COMPONENT DATA

UCS SW 145-H AL 2203377 PHOENIX CONTACT Side panel for use with housing half shells 195 × 145 mm and 145 × 1..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS SW 145-H AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS SW 145-H AL
Catalog number	2203377
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-E68D834E69
Generated	2026-08-05

Product Overview

Side panel for use with housing half shells 195 × 145 mm and 145 × 125 mm in size, panel thickness: 2 mm, total height of housing: 67 mm, material: aluminum

Sidewall for use with housing halves of the sizes: 195x145mm and 145x125mm and 145x125mm, wall thickness 2mm, total housing height: 67mm, material: aluminium

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2203377

Packing unit 1

GTIN 4055626459493

Custom tariff number 76169990

Item properties

Material specifications

Mechanical strength/tumbling barrel

Packaging information

Measurements

Ambient conditions

Test for substances that would hinder coating with paint or varnish

Classifications**Item properties**

Type UCS SW 145-H AL

Order No. 2203377

Housing type Universal housings

Type high

[Back to top](#)Measurements

Width [w] 116 mm

Height [h] 59.5 mm

Depth [d] 2 mm

[Back to top](#)Material specifications

Color (RAL) aluminum color

Housing material Aluminum

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)

[Back to top](#)Mechanical strength/tumbling barrel

Specification IEC 60068-2-31:2008-05

Height of fall 50 cm

Number of drop cycles 50

[Back to top](#)Test for substances that would hinder coating with paint or varnish

Result Test passed

Specification VW PV 3.10.7:2005-02

[Back to top](#)Packaging information

Pieces per package 1

Denomination packing units Pcs.

[Back to top](#)Classifications

eCl@ss

eCl@ss 5.1 27180506

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

[Back to top](#)ETIM

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

[Back to top](#)

ETIM for 2203377 Low-voltage industrial controls and switchgear (EC002779)

Feature Name

Feature Value

Type of enclosure (EF003086)

[Open...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS SW 145-H AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.