

**INDUSTRIAL COMPONENT DATA**

# UCS SW 195-F AL 2203380 PHOENIX CONTACT Side panel for use with housing half shells 237 x 195 mm and 195 x 1..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS SW 195-F AL



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | UCS SW 195-F AL                  |
| Catalog number  | 2203380                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 10 Pcs                           |
| Document ID     | EO-67339BA88A                    |
| Generated       | 2026-08-04                       |

## Product Overview

Side panel for use with housing half shells 237 x 195 mm and 195 x 145 mm in size; panel thickness: 2 mm; total height of housing: 47 mm; material: aluminum

Sidewall for use with housing halves in sizes 237 x 195 mm and 195 x 145 mm; wall thickness 2 mm; total housing height 47 mm; Material: Aluminum

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 2203380

Packing unit 1

GTIN 4055626459707

Custom tariff number 76169990

Item properties

Material specifications

Mechanical strength/tumbling barrel

Packaging information

Measurements

Ambient conditions

Test for substances that would hinder coating with paint or varnish

Classifications

Item properties

Type UCS SW 195-F AL

Order No. 2203380

Housing type Universal housings

Type flat

Back to topMeasurements

Width [ w ] 166 mm

Height [ h ] 39.5 mm

Depth [ d ] 2 mm

Back to topMaterial specifications

Color (RAL) aluminum color

Housing material Aluminum

Back to topAmbient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)

Back to topMechanical strength/tumbling barrel

Specification IEC 60068-2-31:2008-05

Height of fall 50 cm

Number of drop cycles 50

Back to topTest for substances that would hinder coating with paint or varnish

Result Test passed

Specification VW PV 3.10.7:2005-02

Back to topPackaging information

Pieces per package 10

Denomination packing units Pcs.

Back to topClassifications

eCl@ss

eCl@ss 5.1 27180506

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

Back to topETIM

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

Back to top

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS SW 195-F AL with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.