

INDUSTRIAL COMPONENT DATA

UCS SW 237-F 7035 2203385 PHOENIX CONTACT Side panel

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS SW 237-F 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS SW 237-F 7035
Catalog number	2203385
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-8AB1BAAD2E
Generated	2026-08-04

Product Overview

Side panel

Sidewall for use with housing halves size 237 x 195 mm; wall thickness 2 mm; total housing height 47 mm; polycarbonate material; light grey colour similar to RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2203385

Packing unit 10 pc

GTIN 4055626427829

Weight per Piece (excluding packing) 19.000 g

Custom tariff number 85389099

Country of origin DE (Germany)

Item properties

Type UCS SW 237-F 7035

Order No. 2203385

Housing type Universal housings

Type flat

Measurements

Width [w] 208 mm

Height [h] 39.5 mm
Depth [d] 2 mm
Material specifications
Color (RAL) light gray (7035)
Insulating material PC
CTI according to IEC 60112 2
Flammability rating according to UL 94 V0
Housing material PC
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)
Mechanical strength/tumbling barrel
Specification IEC 60068-2-31:2008-05
Height of fall 50 cm
Number of drop cycles 50
Thermostability (ball thrust test)
Specification IEC 60695-10-2:2014-02
Temperature 125 °C
Test duration 1 h
Force 20 N
Test for assessing the risk of fire (glow wire)
Specification DIN EN 60695-2-11 (VDE 0471-2-11):2014-11
Temperature 850 °C
Time of exposure 30 s
Test for substances that would hinder coating with paint or varnish
Result Test passed
Specification VW PV 3.10.7:2005-02
Packaging information
Pieces per package 10
Denomination packing units Pcs.
Standards and regulations
Flammability rating according to UL 94 V0
Classifications
eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 5.0EC001031...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS SW 237-F 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.