

**INDUSTRIAL COMPONENT DATA**

# UCS SW 237-H AL 2203390 PHOENIX CONTACT Side panel for use with housing half shells 237 x 195 mm in size pan..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS SW 237-H AL



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | UCS SW 237-H AL                  |
| Catalog number  | 2203390                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 10 Pcs                           |
| Document ID     | EO-D9221CD07F                    |
| Generated       | 2026-08-04                       |

## Product Overview

Side panel for use with housing half shells 237 x 195 mm in size; panel thickness: 2 mm; total height of housing: 67 mm; material: aluminum

Sidewall for use with housing halves size 237 x 195 mm, wall thickness: 2 mm, total housing height: 67 mm, material: aluminium

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Housing (HS)

## Additional Product Information

Key Commercial Data

Orderkey 2203390

Packing unit 1

GTIN 4055626459738

Custom tariff number 76169990

Item properties

Material specifications

Mechanical strength/tumbling barrel

Packaging information

Measurements

Ambient conditions

Test for substances that would hinder coating with paint or varnish

**Classifications****Item properties**

Type UCS SW 237-H AL

Order No. 2203390

[Back to top](#)Measurements

Width [ w ] 208 mm

Height [ h ] 59.5 mm

Depth [ d ] 2 mm

[Back to top](#)Material specifications

Housing material Aluminum

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)

[Back to top](#)Mechanical strength/tumbling barrel

Specification IEC 60068-2-31:2008-05

Height of fall 50 cm

Number of drop cycles 50

[Back to top](#)Test for substances that would hinder coating with paint or varnish

Result Test passed

Specification VW PV 3.10.7:2005-02

[Back to top](#)Packaging information

Pieces per package 1

Denomination packing units Pcs.

[Back to top](#)Classifications

eCl@ss

eCl@ss 5.1 27180506

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

[Back to top](#)ETIM

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

[Back to top](#)

ETIM for 2203390 Low-voltage industrial controls and switchgear (EC002779)

**Feature Name****Feature Value**

Type of enclosure (EF003086)

Open

Housing connectable (EF003088)

No

Suitable for rail mounting (EF0039...)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS SW 237-H AL with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.