

INDUSTRIAL COMPONENT DATA

UCS WM-B 7035 2203718 PHOENIX CONTACT Adapter for mounting the UCS housing on the wall, material: polyamide,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS WM-B 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS WM-B 7035
Catalog number	2203718
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-54AC24BF43
Generated	2026-08-05

Product Overview

Adapter for mounting the UCS housing on the wall, material: polyamide, color: light gray similar to RAL 7035, used instead of UCS CC corner insert; only used in conjunction with UCS GD 9005 adhesive pad

The adapter for attaching the UCS box to the wall with polyamide material and light grey colour, similar to RAL 7035, is used in place of the UCS CC angle insert, only in combination with the UCS GD 9005 adhesive backing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2203718

Packing unit 1 pc

GTIN 4055626436593

Weight per Piece (excluding packing) 20.000 g

Custom tariff number 39269097

Country of origin DE (Germany)

Item properties

Material specifications

Packaging information

Classifications

Measurements

[Ambient conditions](#)

[Standards and regulations](#)

[Item properties](#)

Type UCS WM-B 7035

Order No. 2203718

Housing type Universal housings

[Back to top](#)[Measurements](#)

Width [w] 16 mm

Height [h] 25.95 mm

Depth [d] 21 mm

Diameter mounting hole 4 mm

[Back to top](#)[Material specifications](#)

Color (RAL) light gray (7035)

Insulating material PA

Flammability rating according to UL 94 V0

Housing material PA

[Back to top](#)[Ambient conditions](#)

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)

[Back to top](#)[Packaging information](#)

Pieces per package 1

Denomination packing units Pcs.

[Back to top](#)[Standards and regulations](#)

Flammability rating according to UL 94 V0

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 5.1 27180506

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

[Back to top](#)[ETIM](#)

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

[Back to top](#)

ETIM for 2203718 Low-voltage industrial controls and switchgear (EC002779)

Feature Name

Feature Value

Type of enclosure (EF003086)

Open

Housing connectable (EF003088)

No

Suitable for rail mounting (EF003972)

No

Wall mounting possible (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS WM-B 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.