

INDUSTRIAL COMPONENT DATA

UCT-WMS 3,2 (12X4) GN CUS 0830208 PHOENIX CONTACT

Conductor marking collar

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-WMS 3,2 (12X4) GN CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT-WMS 3,2 (12X4) GN CUS
Catalog number	0830208
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-2328079599
Generated	2026-08-05

Product Overview

Conductor marking collar

Conductor identification sleeve, available: matted, green, labelled according to customer specifications, mounting class: slip, for terminal width: 5.2 mm, cable diameter range: 1.5 ... 3.2 mm, usable area: 12 x 4 mm, Number of individual indexes: 55
 Driver marking sleeve, Board, to be ordered: as a board, green, printed according to customer specifications, Mounting type: threading, for terminal block pitch: 5.2 mm, Cable diameter range: 1.5 mm ... 3.2 mm, Number of Labels: 55

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > CABINET add-on**

Additional Product Information

Key Commercial Data

Orderkey 0830208

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356629928

Weight per Piece (excluding packing) 14.690 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 12 mm

Width (a) 4.3 mm

Height (c) 5.8 mm

Cable diameter 1.5 mm ... 3.2 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

General

Note Labeled according to customer specifications

Color green

Type Card form

Components free from silicone and halogen

Flammability rating according to UL 94 V0

Material PC V0

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 55

Number of individual labels per row 11

Printability Thermal transfer

Inkjet printing

Device 5146464 THERMOMARK CARD

5147888 BLUEMARK LED

5147999 BLUEMARK CLED

Ink ribbon 5146613 THERMOMARK CARD-UCT-MAG3

0801371 THERMOMARK-RIBBON 110-TC

5147421 BLUEMARK FLUID-CARTRIDGE

5146662 BLUEMARK CLED-FLUID-CARTR.

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type slide on

Result Test passed

Oxygen index (DIN EN ISO 4589...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-WMS 3,2 (12X4) GN CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.