

INDUSTRIAL COMPONENT DATA

UDK 4-MTK 2775265 PHOENIX CONTACT Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UDK 4-MTK



Manufacturer	PHOENIX CONTACT
MPN / Reference	UDK 4-MTK
Catalog number	2775265
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-7AACC7ECA6
Generated	2026-08-02

Product Overview

Knife disconnect terminal block

Knife-interruptible terminal block with double connection on both sides, cross-section: 0.2 - 2.5 mm², AWG: 30 - 10, width: 6.2 mm, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2775265

Packing unit 50 pc

GTIN 4017918068547

Weight per Piece (excluding packing) 16.510 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 4

Nominal cross section 4 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V2

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Nominal current I_N 16 A

Nominal voltage U_N 630 V (At insulation voltages > 500 V all terminal points must be closed with the appropriate tightening torque.)

Open side panel Yes

Dimensions

Width 6.2 mm

Length 63.5 mm

Height NS 35/7,5 47 mm

Height NS 35/15 54.5 mm

Height NS 32 52 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 10

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1 mm²

2 conductors with same cross section, stranded min. 0.2 mm²

2 conductors with sam...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UDK 4-MTK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.