

INDUSTRIAL COMPONENT DATA

UDMTK 5 3048467 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UDMTK 5



Manufacturer	PHOENIX CONTACT
MPN / Reference	UDMTK 5
Catalog number	3048467
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-3887D761D6
Generated	2026-08-05

Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 400 V, nominal current: 10 A, 1st and 2nd floor, connection type: Screw connection, Sizing section: 4 mm², section: 0.2 mm² - 4 mm², 2. Floor, connection type: Screw connection, Sizing section: 4 mm², section: 0.2 mm² - 4 mm², mounting: NS 35/7.5, NS 35/15, NS 32, Color: Gray

Feed-through terminal, rated voltage: 400 V, rated current: 10 A, 1. and 2. Table, Connection type: Screw connection, Dimensioning section: 4 mm², Section: 0.2 mm² - 4 mm², 2. Table, Connection type: Screw connection, Dimensioning section: 4 mm², Section: 0.2 mm² - 4 mm², Mounting: NS 35/7.5, NS 35/15, NS 32, Colour: Grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 3048467

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4046356056021

Weight per Piece (excluding packing) 29.540 g

Custom tariff number 85369010

Country of origin TR (Turkey)

General

Number of levels 2
Number of connections 4
Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current I_N 10 A
Maximum load current 10 A (with 4 mm² conductor cross section)
Nominal voltage U_N 400 V
Open side panel No
Dimensions
Width 6.2 mm
Length 93 mm
Height NS 35/7,5 68.5 mm
Height NS 35/15 76 mm
Height NS 32 73.5 mm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 4 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 1.5 mm²
2 conductors with same cross section, stranded mi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UDMTK 5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.