

**INDUSTRIAL COMPONENT DATA**

# UK 10-DREHSI-EX (6,3X32) 3073966 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 10-DREHSI-EX (6,3X32)



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | PHOENIX CONTACT          |
| MPN / Reference | UK 10-DREHSI-EX (6,3X32) |
| Catalog number  | 3073966                  |
| Category        | Fuse terminal block      |
| Minimum order   | 50 Pcs                   |
| Document ID     | EO-82E710C387            |
| Generated       | 2026-08-06               |

## Product Overview

Fuse modular terminal block

Fuse terminal block, for fuse cartridge G, cross-section: 0.5 - 16 mm<sup>2</sup>, AWG: 24 - 6, width: 12 mm, colour: Black

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

Key Commercial Data

Orderkey 3073966

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356343138

Weight per Piece (excluding packing) 34.760 g

Custom tariff number 85369095

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Nominal cross section 16 mm<sup>2</sup>

Color black

Insulating material PA  
Flammability rating according to UL 94 V2  
Maximum power dissipation for nominal condition 2.43 W  
Fuse G / 6,3 x 32  
Fuse type Glass / ceramics / ...  
Rated surge voltage 4 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Connection in acc. with standard IEC 60947-7-3  
Maximum load current 10 A  
Nominal current IN 10 A  
Nominal voltage UN 400 V  
800 V (As a disconnect terminal block)  
Open side panel No  
Dimensions  
Width 12 mm  
Length 62 mm  
Height NS 35/7,5 57.2 mm  
Height NS 35/15 64.7 mm  
Height NS 32 62.2 mm  
Connection data  
Conductor cross section solid min. 0.5 mm<sup>2</sup>  
Conductor cross section solid max. 16 mm<sup>2</sup>  
Conductor cross section flexible min. 0.5 mm<sup>2</sup>  
Conductor cross section flexible max. 16 mm<sup>2</sup>  
Conductor cross section AWG min. 20  
Conductor cross section AWG max. 6  
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule without plastic sleeve max. 10 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule with plastic sleeve max. 10 mm<sup>2</sup>  
Cross section wit...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 10-DREHSI-EX (6,3X32) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.