

INDUSTRIAL COMPONENT DATA

UK 10,3-CC HESI N 2POL 3048593 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 10,3-CC HESI N 2POL



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 10,3-CC HESI N 2POL
Catalog number	3048593
Category	Fuse terminal block
Minimum order	6 Pcs
Document ID	EO-C550B6BA08
Generated	2026-08-06

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: DC class, rated voltage: 600 V, rated current: 30 A, connection type: Screw connection, Sizing cross-section: 25 mm², cross-section: 1.5 mm²- 25 mm², mounting class: NS 35/7.5, NS 35/15, color: black

Fuse terminal block, Type of fuse: Glass / Ceramic / ..., Fuse type: Class CC, Rated voltage: 600 V, Rated current: 30 A, Connection type: Screw connection, Rated cross-section: 25 mm², Cross-section: 1.5 mm²- 25 mm², Mounting type: NS 35/7.5, NS 35/15, Colour: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3048593

Packing unit 5 pc

Minimum order quantity 5 pc

GTIN 4046356116008

Weight per Piece (excluding packing) 103.000 g

Custom tariff number 85369095

Country of origin DE (Germany)

Note

Trade restriction The products are offered exclusively for export outside the EU and the European Economic Area.

General

Number of levels 1

Number of connections 2

Nominal cross section 25 mm²

Color black

Insulating material PA

Flammability rating according to UL 94 V0

Maximum power dissipation for nominal condition 3.26 W

Fuse Class CC

Fuse type Glass / ceramics / ...

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group IIIb

Maximum load current 32 A (the current and voltage are determined by the fuse)

Nominal current I_N 32 A (the current and voltage are determined by the fuse)

Nominal voltage U_N 690 V (the current and voltage are determined by the fuse)

Open side panel No

Dimensions

Width 36 mm

Length 81 mm

Height NS 35/7,5 65.5 mm

Height NS 35/15 73 mm

Connection data

Conductor cross section solid min. 1.5 mm²

Conductor cross section solid max. 25 mm²

Conductor cross section flexible min. 1.5 mm²

Conductor cross section flexible max. 25 mm²

Conductor cross section AWG min. 16

Conductor cross section AWG max. 4

Conductor cross section flexible, with ferrule without plastic sleeve min. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 16 mm²

Conductor cross section flexible, with ferrul...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 10,3-CC HESI N 2POL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.