

INDUSTRIAL COMPONENT DATA

UK 10,3-CC HESILED N 600 2POL 3048629 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 10,3-CC HESILED N 600 2POL



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 10,3-CC HESILED N 600 2POL
Catalog number	3048629
Category	Fuse terminal block
Minimum order	6 Pcs
Document ID	EO-68E1698638
Generated	2026-08-05

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: DC class, rated voltage: 600 V, rated current: 30 A, connection type: Screw connection, Sizing cross-section: 25 mm², cross-section: 1.5 mm²- 25 mm², mounting class: NS 35/7.5, NS 35/15, color: black

Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: Class CC, nom. voltage: 600 V, nominal current: 30 A, connection method: Screw connection, Rated cross section: 25 mm², cross section: 1.5 mm²- 25 mm², mounting type: NS 35/7,5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataNotesTrade restriction

CE note The products are offered exclusively for export outside the EU and the European Economic Area.

Product propertiesProduct type Fuse terminal block

Number of connections 2

Number of rows 1

Data management status

Article revision 03

Insulation characteristics

Overvoltage category III

Degree of pollution 3
Electrical properties Fuse type Glass / ceramics / ...
Rated surge voltage 6 kV
Maximum power dissipation for nominal condition 4 W
Fuse Class CC
LED voltage range 110 V AC/DC ... 600 V AC/DC
Input data LED voltage range 110 V AC/DC ... 600 V AC/DC
Connection data Number of connections per level 2
Nominal cross section 25 mm²
Screw thread M5
Tightening torque 2 ... 2.5 Nm
Stripping length 11 mm
Internal cylindrical gage B6
Conductor cross section rigid 1.5 mm² ... 25 mm²
Cross section AWG 14 ... 4 (converted acc. to IEC)
Conductor cross section flexible 1.5 mm² ... 25 mm²
Conductor cross section, flexible [AWG] 14 ... 4 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 1.5 mm² ... 16 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 1.5 mm² ... 16 mm²
Cross-section with insertion bridge, rigid 10 mm²
Cross-section with insertion bridge, flexible 10 mm²
2 conductors with same cross section, solid 1.5 mm² ... 4 mm²
2 conductors with same cross section, flexible 1.5 mm² ... 4 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 1.5 mm² ... 4 mm²
2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 10,3-CC HESILED N 600 2POL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.