

INDUSTRIAL COMPONENT DATA

UK 10,3-HESI A 1500V 1069842 PHOENIX CONTACT Fuse modular terminal block, fuse type: Glass / ceramics / ...,,

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 10,3-HESI A 1500V



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 10,3-HESI A 1500V
Catalog number	1069842
Category	Fuse terminal block
Minimum order	12 Pcs
Document ID	EO-2484ED99CF
Generated	2026-08-06

Product Overview

Fuse modular terminal block, fuse type: Glass / ceramics / ..., connection method: Screw connection, cross section: 2.5 mm²- 25 mm², AWG: 14 - 4, nominal current: 32 A, nom. voltage: 1500 V, width: 23 mm, fuse type: gG / gPV / 10.3 x 85, mounting type: NS 35/7,5, NS 35/15, color: black

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: gG / gPV / 10.3 x 85, nominal voltage: 1500 V, nominal current: 32 A, connection type: Screw connection, Sizing cross-section: 16 mm², cross-section: 2.5 mm²- 25 mm², mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 1069842

Packing unit 1 pc

Minimum order quantity 12 pc

Catalog page Page 504 (C-1-2019)

GTIN 4055626747903

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85354000

Country of origin CN (China)

Drawings

Dimensions

Standards and Regulations

Classifications

General

Connection data

Environmental Product Compliance

Drawings

Circuit diagram

[Back to top](#)General

Number of levels 1

Number of connections 2

Nominal cross section 25 mm²

Color black

Insulating material PA

Flammability rating according to UL 94 V0

Maximum power dissipation for nominal condition 6 W

Fuse gG / gPV / 10.3 x 85

Fuse type Glass / ceramics / ...

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Connection in acc. with standard IEC 60269-1 / -2

Maximum load current 32 A (the current and voltage are determined by the fuse)

Nominal current I_N 32 A (the current and voltage are determined by the fuse)

Nominal voltage U_N 1500 V DC

Connection in acc. with standard IEC 60947-1 / -3

Open side panel No

[Back to top](#)Dimensions

Width 23 mm

Length 130 mm

Height NS 35/7,5 65.5 mm

Height NS 35/15 73 mm

[Back to top](#)Connection data

Conductor cross section solid min. 2.5 mm²

Conductor cross section solid max. 25 mm²

Conductor cross section flexible min. 2.5 mm²

Conductor cross section flexible max. 25 mm²

Conductor cross section AWG min. 14

Conductor cross section AWG max. 4

Conductor cross section flexible, with ferrule without plastic....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 10,3-HESI A 1500V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.