

INDUSTRIAL COMPONENT DATA

UK 3-MVSTB-5,08-F 3002335 PHOENIX CONTACT Accessories

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 3-MVSTB-5,08-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 3-MVSTB-5,08-F
Catalog number	3002335
Category	End bracket for terminal block
Minimum order	50 Pcs
Document ID	EO-B1E435137F
Generated	2026-08-06

Product Overview

Accessories

Accessories, pitch: 5.08 mm, mounting class: NS 35/7.5, NS 35/15, NS 32, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3002335

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 323 (CL-2005)

GTIN 4017918090241

Weight per Piece (excluding packing) 5.080 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Color gray

Insulating material PA

Flammability rating according to UL 94 V2

Maximum load current 12 A (with 4 mm² conductor cross section)

Rated surge voltage 4 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Number of positions 1

Connection data

Internal cylindrical gage A3

Standards and Regulations

Flammability rating according to UL 94 V2

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027141100eCl@ss

7.027141135eCl@ss 8.027141135eCl@ss 9.027141135

ETIM 2.0EC000897ETIM 3.0EC000897ETIM 4.0EC000897ETIM 5.0EC001041ETIM 6.0EC001041

UNSPSC 6.0130211811UNSPSC 7.090139121410UNSPSC 1139121410UNSPSC 12.0139121410UNSPSC

13.239121425

ETIM for 3002335 Terminal blocks (EC001041)

Feature Name

Feature Value

Colour (EF000007)

Grey

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Inflammability class of insulation material according to UL94 (EF002521)

V2

Height (EF000040)

48 mm

Depth (EF000049)

47 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 3-MVSTB-5,08-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.