

INDUSTRIAL COMPONENT DATA

UK 3 N GN 0719142 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 3 N GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 3 N GN
Catalog number	0719142
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-C8B15E85FE
Generated	2026-08-05

Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 800 V, nominal current: 24 A, number of connections: 2, connection type: Screw connection, Sizing cross-section: 2.5 mm², cross-section: 0.2 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, color: green

Feed-through terminal block, nom. voltage: 800 V, nominal current: 24 A, number of connections: 2, connection method: Screw connection, Rated cross section: 2.5 mm², cross section: 0.2 mm² - 4 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Feed-through terminal block

Number of connections 2

Number of rows 1

Potentials 1

Data management status

Article revision 13

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Rated surge voltage 8 kV

Maximum power dissipation for nominal condition 0.77 W

Connection data Number of connections per level 2

Nominal cross section 2.5 mm²

Level 1 above 1 below 1

Screw thread M3

Tightening torque 0.6 ... 0.8 Nm

Stripping length 8 mm

Connection in acc. with standard IEC 60947-7-1

Conductor cross section rigid 0.2 mm² ... 4 mm²

Cross section AWG 24 ... 12 (converted acc. to IEC)

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section, flexible [AWG] 24 ... 14 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 2.5 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 1.5 mm²

Cross-section with insertion bridge, rigid 4 mm²

Cross-section with insertion bridge, flexible 2.5 mm²

2 conductors with same cross section, solid 0.2 mm² ... 1.5 mm²

2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²

2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1 mm²

Nominal current 24 A

Maximum load current 32 A (with 4 mm² conductor cross section)

Nomi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 3 N GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.