

INDUSTRIAL COMPONENT DATA

UK 35 TEILBESTUECKT 0711399 PHOENIX CONTACT

Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 35 TEILBESTUECKT



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 35 TEILBESTUECKT
Catalog number	0711399
Category	Feed-through terminal block
Minimum order	25 Pcs
Document ID	EO-C47915CEB1
Generated	2026-08-05

Product Overview

Feed-through terminal block

Feed-through terminal, The terminal block has only one screw, nominal voltage: 1000 V, nominal current: 150 A, connection type: Screw connection, number of connections: 1, cross-section: 0.75 mm² - 50 mm², AWG: 18 - 1/0, width: 16 mm, color: gray, mounting class: NS 35/7.5, NS 35/15, NS 32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0711399

Packing unit 25 pc

Minimum order quantity 25 pc

Note Made to Order (non-returnable)

GTIN 4017918320614

Weight per Piece (excluding packing) 48.960 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 1

Potentials 1

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum load current 150 A (with 50 mm² conductor cross section)Nominal current I_N 150 ANominal voltage U_N 1000 V

Open side panel No

Dimensions

Width 16 mm

Length 50 mm

Height NS 35/7,5 62 mm

Height NS 35/15 69.5 mm

Height NS 32 67 mm

Connection data

Connection method Screw connection

Connection in acc. with standard IEC 60947-7-1

Conductor cross section solid min. 0.75 mm²Conductor cross section solid max. 50 mm²

Conductor cross section AWG min. 18

Conductor cross section AWG max. 1/0

Conductor cross section flexible min. 0.75 mm²Conductor cross section flexible max. 35 mm²

Min. AWG conductor cross section, flexible 18

Max. AWG conductor cross section, flexible 2

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.75 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 35 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.75 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 35 mm²

2 conduct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 35 TEILBESTUECKT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.