

INDUSTRIAL COMPONENT DATA

UK 5-HESI YE/YE 3072190 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 5-HESI YE/YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 5-HESI YE/YE
Catalog number	3072190
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-4C0EF5946B
Generated	2026-08-06

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20/5 x 25/5 x 30, nominal voltage: 800 V, nominal current: 6.3 A, connection type: Screw connection, Sizing cross-section: 1 mm², cross-section: 0.2 mm²- 4 mm², mounting type: NS 35/7.5, NS 35/15, NS 32, colour: yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3072190

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356315302

Weight per Piece (excluding packing) 18.500 g

Custom tariff number 85369095

Country of origin TR (Turkey)

General

Note For terminal marking, please use marking material with 8.2 mm pitch.

For lever marking, please use marking material with 6.2 mm pitch.

Number of levels 1
Number of connections 2
Nominal cross section 4 mm²
Color yellow
Insulating material PA
Flammability rating according to UL 94 V2
Maximum power dissipation for nominal condition 1.02 W
Fuse G / 5 x 20 / 5 x 25 / 5 x 30
Fuse type Glass / ceramics / ...
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-3
Maximum load current 6.3 A
Nominal current I_N 6.3 A
Nominal voltage U_N 800 V (As a fuse terminal block)
Rated operating voltage 250 V
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 1, class B, body mounted
Test frequency f₁= 5 Hz to f₂= 150 Hz
ASD level 1.857 (m/s²)²/Hz
Acceleration 0,8 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specificat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 5-HESI YE/YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.