

INDUSTRIAL COMPONENT DATA

UK 5-MTK-P/P MIT SPERRE 3004087 PHOENIX CONTACT

Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 5-MTK-P/P MIT SPERRE



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 5-MTK-P/P MIT SPERRE
Catalog number	3004087
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-7C58936E3B
Generated	2026-08-04

Product Overview

Knife disconnect terminal block

Blade interruptible terminal block, with threaded sockets for test sockets to accommodate test pins, nominal voltage: 500 V, nominal current: 16 A, 1st floor, connection type: Screw connection, Sizing section: 2.5 mm², cross-section: 0.2 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, NS 32, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3004087

Packing unit 50 pc

GTIN 4017918145613

Weight per Piece (excluding packing) 12.430 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm²

Color gray

Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current I_N 16 A
Maximum load current 16 A (with 4 mm² conductor cross section)
Nominal voltage U_N 500 V
Open side panel No
Dimensions
Width 6.2 mm
Length 51 mm
Height NS 35/7,5 58.5 mm
Height NS 35/15 66 mm
Height NS 32 63.5 mm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 6 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 4 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 10
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Cross section with insertion bridge, solid max. 4 mm²
Cross section with insertion bridge, stranded max. 4 mm²
Connection method Screw connection
Stripping length 8 mm
Internal cylindrical gage...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 5-MTK-P/P MIT SPERRE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.